



Aircraft Wheel & Brake
 Parker Hannifin Corporation
 1160 Center Road
 Avon, Ohio 44011

This document and the information it contains is confidential and proprietary to Parker Hannifin Corporation and its affiliates ("Parker"), may not be copied or disclosed to others or used for any purpose other than conducting business with Parker, and must be returned or destroyed and all further use discontinued at Parker's request. The recipient of this document is advised that improper selection or improper use of Parker systems or components can cause death, personal injury and property damage, and is solely responsible through its own analysis and testing for the final selection of Parker system and components and assuring that all performance endurance, maintenance, safety and warning requirements of the intended application are met. Copyright Parker. Year of copyright is the year(s) indicated on this document. All rights reserved.

PARTS LIST
WHEEL & BRAKE SHIPSET
ORDER CODE: 199-10403
FOR GENERAL USAGE

<u>PART NUMBER</u>	<u>DESCRIPTION</u>	<u>QUANTITY</u>
30-59A	Main Brake Assembly (FAA Approved per TSO C26b)	2
40-59A CHROME	Main Wheel Assembly with chrome disc (FAA Approved per TSO C26b)	2
102-00600	Screw, Dust Shield (FAA TSO Detail Component for 40-59A)	6
157-00900	Dust Shield (FAA TSO Detail Component for 40-59A)	2

Publication Package (P/N PP199-10403) Consists of the following

199-10403 P/L	Parts List for Order Code: 199-10403 (This Document)	1
50-76	Installation Drawing	1
PRM62	Conversion Kit / Chrome Disc Data Sheet	1
PRM13A	Conditioning Procedure for Non-Asbestos Organic Brake Lining	1

NOTES:

- The Cleveland Wheels & Brakes as listed are FAA TSO-C26b approved, quantities are furnished in pairs for replacement of existing equipment on FAA Type Certificated Aircraft (Original Equipment TC Approved or per TC holder Service Bulletin) or initial installation on an experimental non FAA Type Certificated Aircraft.
- Note! For a product to be TSO qualified, it has to have successfully demonstrated its ability to meet minimum performance standards in accordance with FAA recognized rating methods. The TSO approval of a product does not constitute installation approval or applicability on an FAA Type Certificated Aircraft.** It is the responsibility of those installing these products to determine that the aircraft installation and its wheel and brake performance requirements are compatible for the TSO ratings of the wheel and brake. TSO approved products must have separate approval for installation in a FAA type certificated aircraft. TSO Approved Products may be installed only if performed under Title 14 CFR Part 43 or the applicable airworthiness requirements.
- Be advised that number "199-10403" is an Order Code Number only, to identify the grouping of a pre-packaged ship set of TSO Approved wheels and brakes for customer ordering and shipping convenience. At time of installation of parts contained within, the installer is to refer only to the Part Number of each listed wheel and brake assembly to indicate what parts have been installed on the aircraft. Do not refer to the 199-10403 order code number for installation purposes, as it is not an FAA recognized part number.
- "Removed"

Order Code Number 199-10403 P/L
 NC 03-09-1984 (273-63)
 Rev. A 02-08-1985 (275-68)
 Rev. B 05-04-1988 (289-72)
 Rev. C 06-12-2001 (0342-62)
 Rev. D 08-01-2006 (0370-75)
 Rev. E 10-05-2018 (0096929)

EXPORT WARNING - This document contains technical data whose export is restricted by the Arms Export Control Act (Title 22, U.S.C., Sec 2751, et seq.) or the Export Administration Act of 1979 (Title 50, U.S.C., App. 2401, et seq.), as amended. Violations of these export laws are subject to severe criminal penalties. Disseminate in accordance with provisions of DoD Directive 5230.25.

LIMITED RIGHTS
 CONTRACT NO. 790E-74B
 CONTRACTOR NAME: PARKER HANNIFIN CORPORATION
 AIRCRAFT WHEEL AND BRAKE DIVISION
 1150 AVON CENTER ROAD
 AVON, OHIO 44011
 THE GOVERNMENT'S RIGHT TO USE, REPRODUCE, RELEASE, PERFORM, DISPLAY, OR DISCLOSE THESE TECHNICAL DATA ARE RESTRICTED TO THE EXTENT OF THE RIGHTS IN TECHNICAL DATA-NONCOMMERCIAL ITEMS CLAUSE CONTAINED IN THE ABOVE IDENTIFIED CONTRACT. ANY REPRODUCTION OF TECHNICAL DATA OTHER THAN THE GOVERNMENT, WHO HAS BEEN PROVIDED ACCESS TO SUCH DATA MUST PROMPTLY RETURN THE ABOVE DATA TO CONTRACTOR.

THIS DOCUMENT CONTAINS INFORMATION THAT IS CONFIDENTIAL AND PROPRIETARY TO PARKER HANNIFIN CORP. ("PARKER"). THIS DOCUMENT IS FURNISHED ON THE UNDERSTANDING THAT THE DOCUMENT AND THE INFORMATION IT CONTAINS WILL NOT BE COPIED OR DISCLOSED TO OTHERS EXCEPT WITH THE WRITTEN CONSENT OF PARKER. IT WILL NOT BE USED FOR ANY OTHER PURPOSE OTHER THAN CONDUCTING BUSINESS WITH PARKER, AND WILL BE RETURNED AND ALL FURTHER USE DISCONTINUED UPON REQUEST BY PARKER. COPYRIGHT PARKER. YEAR OF COPYRIGHT IS FIRST YEAR INDICATED ON THIS DOCUMENT. ALL RIGHTS RESERVED.

USER INFORMATION

REVISIONS						
CHANGE NOTICE	REV	DESCRIPTION OF CHANGE	CHK BY	DATE	APPROVED	
2342-62	J	REVISED AND REDRAWN. SEE C/J/N	MM	06-12-2001	B. BARKER	
2366-81	K	PRODUCTION CHANGE, SEE C/J/N	RPR	09/09/2005	D. MILLER	
2370-75	L	PRODUCTION CHANGE, SEE C/J/N	GL	08-01-2006	B. BARKER	

THE INFORMATION LISTED ON THIS DRAWING IS FOR REFERENCE PURPOSES ONLY. DIMENSIONAL LIMITS WHERE SHOWN MUST BE MAINTAINED TO OBTAIN PROPER OPERATIONAL CHARACTERISTICS. EQUIPMENT SELECTION AND AIRCRAFT COMPATIBILITY IS THE RESPONSIBILITY OF THE INSTALLER.



ALL WHEELS AND BRAKES SHOWN ARE TSO APPROVED. THEY HAVE BEEN PACKAGED TO OFFER VARIOUS CONFIGURATIONS ACCORDING TO BRAKE KINETIC ENERGY (KE) AND WHEEL STATIC LOAD CAPACITIES. SELECT EQUIPMENT PER THE AIRCRAFT MANUFACTURER'S RECOMMENDATIONS OR CALCULATE THE KINETIC ENERGY LEVEL THAT EACH WHEEL & BRAKE ASSEMBLY WILL BE REQUIRED TO ABSORB. USE THIS CALCULATED (KE) VALUE TO SELECT EQUIPMENT OF PROPER CAPACITY. KINETIC ENERGY REQUIREMENTS FOR THE AIRCRAFT MAY BE CALCULATED AS FOLLOWS (REFERENCE FAR PART 23.735):

$$KE = \frac{.0443 \times W \times V \times V}{N}$$

WHERE: KE = KINETIC ENERGY PER WHEEL-BRAKE ASSEMBLY (FT-LBS)
 W = DESIGN LANDING WEIGHT (LBS)
 V = AIRCRAFT SPEED IN KNOTS. V MUST BE NOT LESS THAN VSO, THE POWEROFF STALLING SPEED OF THE AIRCRAFT AT SEA LEVEL, AT THE DESIGN LANDING CONFIGURATION.
 N = NUMBER OF WHEELS WITH BRAKES.

ANY UNAUTHORIZED MODIFICATIONS OF EQUIPMENT WITHOUT THE EXPRESS WRITTEN CONSENT OF PARKER HANNIFIN CORP., AIRCRAFT WHEEL & BRAKE WILL VOID ALL WARRANTIES AND TSO APPROVALS.

FOR ADDITIONAL INFORMATION CONTACT CUSTOMER SUPPORT, 440-937-1272 OR FAX 440-937-5409. WEBSITE: WWW.PARKER.COM/CLEVELAND TECHNICAL SERVICES HOTLINE: 1-800-BRAKING (272-5464).



SHIP SET NUMBER	DESCRIPTION MAGNESIUM = MAG. ALUMINUM = ALUM.	WHEEL ASSEMBLY A	TIRE SIZE & PLY. RATING	TORQUE WHEEL NUTS 3 B	TIRE INFLATION PRESSURE 5	STATIC LOAD CAPACITY 6	KINETIC ENERGY CAPACITY 6	BEARING DIA. C	BEARING SPACING D	AXLE SPACING E	MAX ROTATING PARTS F	BRAKE ASSEMBLY 7 G	DRY TORQUE TIE BOLTS H	BOLT HOLE LOCATION I I1	BOLT HOLE LOCATION J J1	TORQUE PLATE CENTER HOLE DIA. K	BOLT HOLE DIA. L	TOTAL KIT WGT. LESS TUBE & TIRE
199-10200 OR 199-10203	5.00-5 MAG. WHEEL ALUM. BRAKE	40-78B	5.00-5 6 PLY.	90 IN-LBS.	31 PSI	1260 LBS.	117,500 FT-LB	1.2505 1.2500	3.034 2.992	.947	1.495	30-9 8	90 IN-LBS.	.470 .847 .847 .470	1.377/1.379	.255-.262 8 PLACES	10.80 LBS.	
199-10300 OR 199-10303	5.00-5 ALUM. WHEEL ALUM. BRAKE	40-78J 40-78A CHROME	5.00-5 6 PLY.	90 IN-LBS.	31 PSI	1260 LBS.	117,500 FT-LB	1.2505 1.2500	3.034 2.992	.947	1.495	30-9C 8	90 IN-LBS.	.470 .847 .847 .470	1.377/1.379	.255-.262 8 PLACES	12.40 LBS.	
199-10400 OR 199-10403	6.00-6 MAG. WHEEL MAG. BRAKE	40-59A 40-59A CHROME	6.00-6 6 PLY.	150 IN-LBS.	42 PSI	1750 LBS.	185,000 FT-LB	1.5005 1.5000	3.292 3.250	1.659	2.207	30-59A	90 IN-LBS.	.562 — .974 —	1.675/1.685	.375-.382 4 PLACES	16.36 LBS.	
199-10500 OR 199-10503	6.00-6 ALUM. WHEEL ALUM. BRAKE	40-113X 40-113X CHROME	6.00-6 6 PLY.	90 IN-LBS.	37 PSI	1500 LBS.	200,000 FT-LB	1.5005 1.5000	3.292 3.250	1.658	2.216	30-75X	90 IN-LBS.	.562 — .974 —	1.675/1.685	.375-.382 4 PLACES	19.20 LBS.	
199-15200	5.00-5 MAG. WHEEL MAG. BRAKE	40-151	5.00-5 6 PLY.	90 IN-LBS.	50 PSI	1260 LBS.	192,000 FT-LB	1.2505 1.2500	3.034 2.992	1.105	1.653	30-133 8	75-80 IN-LBS.	.470 .847 .847 .470	1.377/1.379	.255-.262 8 PLACES	14.00 LBS.	
199-15201	5.00-5 ALUM. WHEEL MAG. BRAKE	40-151A	5.00-5 6 PLY.	90 IN-LBS.	50 PSI	1260 LBS.	192,000 FT-LB	1.2505 1.2500	3.034 2.992	1.105	1.653	30-133 8	75-80 IN-LBS.	.470 .847 .847 .470	1.377/1.379	.255-.262 8 PLACES	15.80 LBS.	
199-15600	5.00-5 MAG. WHEEL ALUM. BRAKE	40-230	5.00-5 6 PLY.	90 IN-LBS.	50 PSI	1260 LBS.	155,000 FT-LB	1.2505 1.2500	3.034 2.992	1.060	1.608	30-181A 8	75-80 IN-LBS.	.470 .847 .847 .470	1.377/1.379	.255-.262 8 PLACES	12.50 LBS.	
199-19700	5.00-5 MAG. WHEEL MAG. BRAKE	40-151	5.00-5 6 PLY.	90 IN-LBS.	50 PSI	1260 LBS.	289,000 FT-LB	1.2505 1.2500	3.034 2.992	1.105	1.653	30-164 8	75-80 IN-LBS.	.470 .847 .847 .470	1.377/1.379	.255-.262 8 PLACES	14.10 LBS.	
199-20400	6.00-6 MAG. WHEEL MAG. BRAKE	40-281	7.00-6 6 PLY.	90 IN-LBS.	38 PSI	1200 LBS.	141,115 FT-LB	1.2505 1.2500	3.625 3.583	1.645	2.193	30-214 8	75-80 IN-LBS.	.562 I2 1.125	.974 C	1.675/1.685	.255-.262 6 PLACES	16.18 LBS.
199-22300	6.00-6 MAG. WHEEL MAG. BRAKE	40-281	7.00-6 6 PLY.	90 IN-LBS.	38 PSI	1200 LBS.	141,115 FT-LB	1.2505 1.2500	3.625 3.583	1.645	2.193	30-214B 8	75-80 IN-LBS.	.470 .847 .847 .470	1.3790/1.3818	.255-.262 8 PLACES	17.63 LBS.	

- NOTES:**
- 1 ROTATIONALLY ORIENTATE BRAKE CYLINDER TO PROVIDE GROUND CLEARANCE AND FLAT OR DEFLECTED TIRE SIDEWALL CLEARANCE.
 - 2 WHEEL & BRAKE COMPATIBLE FOR USE WITH FOLLOWING TUBE TYPE TIRES:
6.00-6 (4 OR 6 PLY.)
8.00-6 (6 OR 8 PLY.)
 - 3 TORQUE VALUES SHOWN ARE "FINAL DRY NUT TORQUES".
 - 4 DUST SHIELDS PROVIDED FOR ALL SHIP SETS EXCEPT 199-20400 AND 199-22300.
 - 5 MAXIMUM TIRE INFLATION PRESSURE: OVER INFLATION MAY RESULT IN EXPLOSIVE FAILURE OR REDUCED WHEEL SERVICE LIFE. INFLATION PRESSURE MAY BE ADJUSTED DOWN TO OBTAIN DESIRED FLATOTATION FOR SPECIFIC AIRCRAFT WEIGHT AND OPERATING ENVIRONMENT.
 - 6 CAPACITIES SHOWN ARE FOR EACH WHEEL & BRAKE ASSEMBLY. AT A NORMAL DECELERATION RATE OF 10 FT/SEC-SEC.
 - 7 SEAL IS COMPATIBLE WITH MIL-H-5606 OR MIL-H-83282 HYDRAULIC FLUID.
 - 8 TORQUE PLATE MOUNTING HOLE LOCATIONS PROVIDE FOR SIMILAR ROTATIONAL ORIENTATION BETWEEN THE LEFT & RIGHT BRAKE ASSEMBLIES. TORQUE PLATE TO BE ATTACHED TO STRUCTURE USING A MINIMUM OF (4) .250 DIAMETER BOLTS.
 - 9 TORQUE PLATE HOLE MOUNTING CONFIGURATION MATCHES THE SAME HOLE PATTERN AS THE TORQUE PLATE USED IN THE 199-10200 AND 199-10300 KITS. THE 199-22300 KIT MAY BE USED TO UPGRADE AN AIRCRAFT EQUIPPED WITH 199-10200 AND 199-10300 KIT PROVIDED THE EQUIPMENT IS COMPATIBLE WITH THE AIRCRAFT AND THE AXLE IS CHANGED TO ACCOMODATE THE 6.00-6 WHEEL PER THE DIMENSIONAL REQUIREMENTS SHOWN.
 - 10 HIGH CORROSION CONVERSION KIT: WHEEL ASSEMBLY CONTAINS CHROME CUPS & CONES AND CORROSION RESISTANT BRAKE DISC.

GENERAL NOTES: UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES THIRD ANGLE PROJECTION
 TOLERANCES: 2 PLACE (+ .XX); - .03
 3 PLACE (+ .XXX); - .010
 ANGULAR DIMS: +0.5°
 REMOVE ALL BURRS
 BREAK CORNERS: 010 MAX.
 INTERNAL RADI: .005-.010
 GENERAL MACHINED SURFACES: 125 PER ANSI B46.1
 RAW MATERIAL:

QTY FINAL ASSY QTY NEXT ASSY
 APPLICATION (NOT MAINTAINED)
 DIMENSIONING AND TOLERANCING PER ASME Y14.5M-1994
 UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS APPLY AFTER HEAT TREATING, PLATING, AND BEFORE PAINTING.
 THIS PLOT IS COMPLETELY DEFINED BY THE COMPUTER DATASET, WHICH IS THE SOLE AUTHORITY FOR THE INFORMATION PROVIDED. DIMENSIONALLY STABLE COPIES MUST BE OBTAINED FROM THE DATASET. ALL REVISIONS TO THIS PLOT MUST BE BY DATASET REVISION ONLY - NO REVISIONS MAY BE MADE BY HAND.

PROGRAM/CONTRACT NO. 790E-74B
 DRAWN: R. SCHERRY
 CHECKED: []
 ENGINEER: []
 DATE: 5-28-81
 DWG. TITLE: KIT INFORMATION
 SIZE: E
 CAGE CODE: E13269
 DWG. NO.: 50-76
 SCALE: 1/1
 UNIT WGT.: []
 SHEET: 1 OF 1

Cleveland

Wheels & Brakes

Parker Hannifin Corporation

Aircraft Wheel & Brake

1160 Center Road

Avon, Ohio 44011 USA

1-800-BRAKING (272-5464)

216-937-1272 • FAX 216-937-5409

PRODUCT REFERENCE MEMO

CONDITIONING PROCEDURE FOR NON ASBESTOS ORGANIC BRAKE LINING

The brake lining material used in this brake assembly is a non asbestos organic composition. This material must be properly conditioned in order to provide maximum performance and service life.

Conditioning may be accomplished as follows:

1. Taxi aircraft for 1500 feet with engine at 1700 rpm applying brake pedal force as needed to develop a 5 - 10 mph taxi speed.
2. Allow brakes to cool for 10 - 15 minutes.
3. Apply brakes and check to see if a high throttle static run up may be held with normal pedal force. If so, conditioning is completed.
4. If static run up cannot be held, repeat steps 1 through 3 as needed to successfully hold.

This conditioning procedure will generate sufficient heat to create a thin layer of glazed material at the lining friction surface. Normal brake usage should generate enough heat to maintain the glaze throughout the life of the lining.

Light brake usage can cause the glaze to wear off, resulting in reduced brake performance. In such cases, the lining may be conditioned again following the instructions set forth in this PRM.